

ATACR™

1-8x24mm F1



Magnification range	1-8x	Eye relief	3.7 in/95 mm
Focal plane	First	Field of view @ 100 yd/m	1x: 96.1 ft/32.0 m 8x: 13.1 ft/4.4 m
Body tube diameter	34 mm	Exit pupil	1x: 11.3 mm 8x: 3.2 mm
Overall length	10.1 in/256 mm	Illumination	Daylight visible, externally adjustable, two night vision compatible settings
Mounting length	5.7 in/144 mm	Elevation feature	Capped, finger adjustable
Weight	21.0 oz/595 g	Power Throw Lever	Standard
Click value	.1 MRAD	Reticles available	FC-DMX™ 
Internal adjustment range	E: 30 MRAD W: 30 MRAD		
Parallax adjustment	Fixed @ 125 m		

ATACR™

4-16x42mm F1



Magnification range	4-16x	Eye relief	3.5 in/90 mm
Focal plane	First	Field of view @ 100 yd/m	4x: 26.9 ft/9.0 m 16x: 6.9 ft/2.3 m
Body tube diameter	34 mm	Exit pupil	4x: 10.3 mm 16x: 2.7 mm
Overall length	12.6 in/320 mm	Illumination	Digillum
Mounting length	6.3 in/160 mm	Elevation feature	ZeroHold
Weight	30.0 oz/850 g	Power Throw Lever	Standard
Click value	.250 MOA or .1 MRAD	Reticles available	MOAR™  MOA-XT™  MIL-C™  MIL-R™  MIL-XT™  TREMOR3™ 
Internal adjustment range	E: 89 MOA/26 MRAD W: 60 MOA/18 MRAD		
Parallax adjustment	45 yd—∞		

ATACR™

4-16x50mm



Magnification range	4-16x	Eye relief	3.5 in/89 mm
Focal plane	Second	Field of view @ 100 yd/m	4x: 26.9 ft/9.0 m 16x: 6.9 ft/2.3 m
Body tube diameter	34 mm	Exit pupil	4x: 9.5 mm 16x: 3.2 mm
Overall length	13.1 in/333 mm	Illumination	Digillum
Mounting length	6.3 in/161 mm	Elevation feature	ZeroStop
Weight	33.3 oz/944 g	Power Throw Lever	Standard
Click value	.250 MOA or .1 MRAD	Reticles available	MOAR™ ● MIL-R™ ●
Internal adjustment range	E: 110 MOA/30 MRAD W: 60 MOA/16 MRAD		
Parallax adjustment	45 yd—∞		

ATACR™

4-20x50mm F1



Magnification range	4-20x	Eye relief	3.5 in/90 mm
Focal plane	First	Field of view @ 100 yd/m	4x: 23.6 ft/7.9 m 20x: 6.1 ft/2.0 m
Body tube diameter	34 mm	Exit pupil	4x: 8.3 mm 20x: 2.5 mm
Overall length	13.9 in/353 mm	Illumination	Digillum
Mounting length	5.9 in/150 mm	Elevation feature	ZeroStop
Weight	35.2 oz/998 g	Power Throw Lever	Standard
Click value	.250 MOA or .1 MRAD	Reticles available	MOAR™ ● MOA-XT™ ● MIL-C™ MIL-XT™ ● TREMOR3™ ●
Internal adjustment range	E: 130 MOA/38 MRAD W: 100 MOA/29 MRAD		
Parallax adjustment	11 yd—∞		

ATACR™

5-25x56mm F1



Magnification range	5-25x	Field of view @ 100 yd/m	5x: 18.7 ft/6.2 m 25x: 4.9 ft/1.6 m
Focal plane	First	Exit pupil	5x: 8.3 mm 25x: 2.3 mm
Body tube diameter	34 mm	Illumination	Digillum
Overall length	15.4 in/390 mm	Elevation feature	ZeroStop
Mounting length	5.9 in/150 mm	Power Throw Lever	Standard
Weight	37.6 oz/1066 g	Reticles available	MOAR™ ● MIL-C™ MIL- R™ MIL-XT™ ● TREMOR3™ ● MOA-XT™ ●
Click value	.250 MOA or .1 MRAD		
Internal adjustment range	E: 120 MOA/35 MRAD W: 80 MOA/24 MRAD		
Parallax adjustment	45 yd-∞		
Eye relief	3.5 in/90 mm		

ATACR™

5-25x56mm



Magnification range	5-25x	Eye relief	3.5 in/90 mm
Focal plane	Second	Field of view @ 100 yd/m	5x: 18.0 ft/6.0 m 25x: 4.9 ft/1.6m
Body tube diameter	34 mm	Exit pupil	5x: 10.5 mm 25x: 2.2 mm
Overall length	14.3 in/363 mm	Illumination	Digillum
Mounting length	6.1 in/156 mm	Elevation feature	ZeroStop
Weight	39.1 oz/1108 g	Power Throw Lever	Standard
Click value	.250 MOA or .1 MRAD	Reticles available	MOAR™ ● MOAR-T™ ● MIL-R™ ●
Internal adjustment range	E: 120 MOA/35 MRAD W: 60 MOA/17 MRAD		
Parallax adjustment	45 yd-∞		

