

COMPETITION™

15-55x52mm



Magnification range	15-55x	Eye relief	3.2 in/81 mm
Focal plane	Second	Field of view @ 100 yd/m	15x: 6.9 ft/2.3 m 55x: 1.8 ft/0.6 m
Body tube diameter	30 mm	Exit pupil	15x: 3.5 mm 55x: 0.9 mm
Overall length	16.2 in/411 mm	Illumination	Non-illuminated
Mounting length	6.4 in/162 mm	Elevation feature	ZeroStop™
Weight	27.9 oz/790 g	Throw Lever	N/A
Click value	.125 MOA	Reticles available	CTR-2™ ● CTR-3™ ● DDR-2™ ● FCR-1™ ●
Internal adjustment range	E: 55 MOA W: 50 MOA		
Parallax adjustment	25 yd—∞		

PRECISION BENCHREST

8-32x56mm



Magnification range	8-32x	Eye relief	3.0 in/75 mm
Focal plane	Second	Field of view @ 100 yd/m	8x: 9.4 ft/3.1 m 32x: 3.1 ft/1.0 m
Body tube diameter	30 mm	Exit pupil	8x: 5.6 mm 32x: 1.7 mm
Overall length	16.6 in/422 mm	Illumination	Analog
Mounting length	5.5 in/140 mm	Elevation feature	Capped, finger adjustable
Weight	36.0 oz/1021 g	Power Throw Lever	N/A
Click value	.125 MOA	Reticles available	NP-R2™ ●
Internal adjustment range	E: 50 MOA W: 50 MOA		
Parallax adjustment	25 yd—∞		

PRECISION BENCHREST

12-42x56mm



Magnification range	12-42x	Eye relief	3.0 in/75 mm
Focal plane	Second	Field of view @ 100 yd/m	12x: 6.7 ft/2.2 m 42x: 2.3 ft/0.8 m
Body tube diameter	30 mm	Exit pupil	12x: 4.0 mm 42x: 1.4 mm
Overall length	17.0 in/432 mm	Illumination	Analog
Mounting length	5.9 in/150 mm	Elevation feature	Capped, finger adjustable
Weight	36.0 oz/1021 g	Power Throw Lever	N/A
Click value	.125 MOA	Reticles available	NP-R2™ ● NP-2DD™ ●
Internal adjustment range	E: 40 MOA W: 40 MOA		
Parallax adjustment	25 yd-∞		