



3-10x42mm



Magnification range	3-10x	Eye relief	3.5 in/88 mm
Focal plane	Second	Field of view @ 100 yd/m	3x: 34.9 ft/11.6 m 10x: 11.0 ft/3.7 m
Body tube diameter	30 mm	Exit pupil	3x: 10.7 mm 10x: 4.4 mm
Overall length	11.6 in/295 mm	Illumination	Analog
Mounting length	5.1 in/130 mm	Elevation feature	Capped, finger adjustable
Weight	22.2 oz/629 g	Power Throw Lever	Accessory
Click value	.250 MOA	Reticles available	MOAR™ ● Forceplex™ ● (N. Amer.) ● 4A (Int'l only) ●
Internal adjustment range	E: 90 MOA W: 80 MOA		
Parallax adjustment	Fixed @ 125 yd		



4-14x50mm F1



Magnification range	4-14x	Eye relief	3.1 in/80 mm
Focal plane	First	Field of view @ 100 yd/m	4x: 25.1 ft/8.4 m 14x: 7.4 ft/2.5 m
Body tube diameter	30 mm	Exit pupil	4x: 10.8 mm 14x: 3.3 mm
Overall length	14.8 in/376 mm	Illumination	Analog
Mounting length	6.1 in/155 mm	Elevation feature	Zero SET
Weight	30.0 oz/850 g	Power Throw Lever	Accessory
Click value	.250 MOA or .1 MRAD	Reticles available	MOAR™ ● MIL-R™ ● MIL-XT™ ●
Internal adjustment range	E: 90 MOA/27 MRAD W: 70 MOA/19 MRAD		
Parallax adjustment	25 yd-∞		



4-14x56mm



Magnification range	4-14x	Eye relief	3.6 in/92 mm
Focal plane	Second	Field of view @ 100 yd/m	4x: 24.9 ft/8.3 m 14x: 7.3 ft/2.2 m
Body tube diameter	30 mm	Exit pupil	4x: 12.0 mm 14x: 3.6 mm
Overall length	14.8 in/376 mm	Illumination	Analog (Optional)
Mounting length	5.8 in/147 mm	Elevation feature	Capped, finger adjustable
Weight	26.9 oz/763 g (non-illum) 28.5 oz/808 g (illum)	Power Throw Lever	Accessory
Click value	.250 MOA	Reticles available	MOAR™ ● 4A (Int'l only) ●
Internal adjustment range	E: 90 MOA W: 70 MOA		
Parallax adjustment	25 yd—∞		



5-20x56mm



Magnification range	5-20x	Eye relief	3.5 in/90 mm
Focal plane	Second	Field of view @ 100 yd/m	5x: 17.9 ft/6.0 m 20x: 5.0 ft/1.7 m
Body tube diameter	30 mm	Exit pupil	5x: 8.7 mm 20x: 2.5 mm
Overall length	15.2 in/386 mm	Illumination	Analog (Optional)
Mounting length	6.5 in/165 mm	Elevation feature	Zero SET
Weight	29.1 oz/825 g (non-illum) 30.5 oz/865 g (illum)	Power Throw Lever	Accessory
Click value	.250 MOA	Reticles available	MOAR™ ● Forceplex™ ● (N. Amer.) 4A ● (Int'l only) ●
Internal adjustment range	E: 80 MOA W: 50 MOA		
Parallax adjustment	25 yd—∞		